






HTML Tags list

Tag name	Description
<u><!-- --></u>	This tag is used to apply comments in an HTML document.
<u><!DOCTYPE></u>	This tag is used to specify the version of HTML
A	
<u><a></u>	It is termed as an anchor tag and it creates a hyperlink or link.
<u><abbr></u>	It defines an abbreviation for a phrase or longer word.
<u><acronym></u>	It defines an acronym for a word. (Not supported in HTML5)
<u><address></u>	It defines the author's contact information of the HTML article
<u><applet></u>	It defines an embedded Java applet. (Not supported in HTML5)
<u><area></u>	It defines the area of an image map.
<u><article></u> 	It defines the self-contained content.
<u><aside></u> 	It defines content aside from main content. Mainly represented as a sidebar.

<audio> 	It is used to embed sound content in HTML documents.
<h2>B</h2>	
	It is used to make a text bold.
<base>	This tag defines the base URL for all relative URLs within the document.
<basefont>	This tag is used to set the default font, size and color for all elements of the document. (Not supported in HTML5)
<bdi> 	This tag is used to provide isolation for that part of text which may be formatted in different directions from its surrounding text.
<bdo>	It is used to override the current text direction.
<big>	This tag is used to make font size one level larger than its surrounding content. (Not supported in HTML5)
<blockquote>	It is used to define a content which is taken from another source.
<body>	It is used to define the body section of an HTML document.

	It is used to apply single line break.
<button>	It is used to represent a clickable button

C

[<canvas>](#)  It is used to provide a graphics space within a web document.

[<caption>](#) It is used to define a caption for a table.

[<center>](#) It is used to align the content in the center. **(Not supported in HTML5)**


[<cite>](#) It is used to define the title of the work, book, website, etc.

[<code>](#) It is used to display a part of programming code in an HTML document.




[<col>](#) It defines a column within a table which represents common properties of columns and is used with the `<colgroup>` element.

[<colgroup>](#) It is used to define a group of columns in a table.

D


[<data>](#)  It is used to link the content with the machine-readable translation.


[<datalist>](#)  It is used to provide a predefined list for input option.

<u><dd></u>	It is used to provide definition/description of a term in description list.
<u></u>	It defines a text which has been deleted from the document.
<u><details></u> 	It defines additional details which the user can either view or hide.
<u><dfn></u>	It is used to indicate a term which is defined within a sentence/phrase.
<u><dialog></u> 	It defines a dialog box or other interactive components.
<u><dir></u>	It is used as a container for a directory list of files. (Not supported in HTML5)
<u><div></u>	It defines a division or section within an HTML document.
<u><dl></u>	It is used to define a description list.
<u><dt></u>	It is used to define a term in a description list.
E	
<u></u>	It is used to emphasize the content applied within this element.
<u><embed></u> 	It is used as an embedded container for external file/application/media, etc.


F

[<fieldset>](#) It is used to group related elements/labels within a web form.

[<figcaption>](#)
 It is used to add a caption or explanation for the <figure> element.

[<figure>](#)  It is used to define the self-contained content, and mostly refer to a single unit.

[](#) It defines the font, size, color, and face for the content. **(Not supported in HTML5)**

[<footer>](#)  It defines the footer section of a webpage.


[<form>](#) It is used to define an HTML form.



[<frame>](#) It defines a particular area of a webpage which can contain another HTML file. **(Not supported in HTML5)**




[<frameset>](#) It defines a group of Frames. **(Not supported in HTML5)**

H



[<h1> to <h6>](#) It defines headings for an HTML document from level 1 to level 6.

<u><head></u>	It defines the head section of an HTML document.
<u><header></u> 	It defines the header of a section or webpage.
<u><hr></u>	It is used to apply thematic break between paragraph-level elements.
<u><html></u>	It represents the root of an HTML document.
I	
<u><i></u>	It is used to represent a text in some different voice.
<u><iframe></u>	It defines an inline frame which can embed other content.
<u></u>	It is used to insert an image within an HTML document.
<u><input></u>	It defines an input field within an HTML form.
<u><ins></u>	It represents text that has been inserted within an HTML document.
<u><isindex></u>	It is used to display search strings for current documents. (Not supported in HTML5)
K	

<u><kbd></u>	It is used to define keyboard input.
L	
<u><label></u>	It defines a text label for the input field of form.
<u><legend></u>	It defines a caption for content of <fieldset>
<u></u>	It is used to represent items in a list.
<u><link></u>	It represents a relationship between the current document and an external resource.
M	
<u><main></u> 	It represents the main content of an HTML document.
<u><map></u>	It defines an image map with active areas.
<u><mark></u> 	It represents a highlighted text.
<u><marquee></u>	It is used to insert the scrolling text or an image either horizontally or vertically. (Not supported in HTML5)
<u><menu></u>	It is used for creating a menu list of commands.
<u><meta></u>	It defines metadata of an HTML document.

<u><meter></u> 	It defines scalar measurement with known range or fractional value.
<h2>N</h2>	
<u><nav></u> 	It represents a section of the page to represent navigation links.
<u><noframes></u>	It provides alternate content to represent in the browser which does not support the <frame> elements. (Not supported in HTML5)
<u><noscript></u>	It provides an alternative content if a script type is not supported in the browser.
<h2>O</h2>	
<u><object></u>	It is used to embed an object in an HTML file.
<u></u>	It defines an ordered list of items.
<u><optgroup></u>	It is used to group the options of a drop-down list.
<u><option></u>	It is used to define options or items in a drop-down list.
<u><output></u> 	It is used as a container element which can show the result of a calculation.


P

<p>	It represents a paragraph in an HTML document.
<param>	It defines parameter for an <object> element
<picture> 	It defines more than one source element and one image element.
<pre>	It defines preformatted text in an HTML document.
<progress> 	It defines the progress of a task within an HTML document.



Q


<q>	It defines short inline quotations.
---------------------------	-------------------------------------



R

<rp> 	It defines an alternative content if the browser does not support ruby annotations.
<rt>	It defines explanations and pronunciations in ruby annotations.
<ruby>	It is used to represent ruby annotations.

S

<u><s></u>	It renders text which is no longer correct or relevant.
<u><samp></u>	It is used to represent sample output of a computer program.
<u><script></u>	It is used to declare the JavaScript within an HTML document.
<u><section></u> 	It defines a generic section for a document.
<u><select></u>	It represents a control which provides a menu of options.
<u><small></u>	It is used to make text font one size smaller than the document's base font size.
<u><source>></u> 	It defines multiple media resources for different media elements such as <picture>, <video>, and <audio> element.
<u></u>	It is used for styling and grouping inline.
<u><strike></u>	It is used to render strikethrough the text. (Not supported in HTML5)
<u></u>	It is used to define important text.
<u><style></u>	It is used to contain style information for an HTML document.
<u><sub></u>	It defines a text which displays as a subscript text.

<summary> 	It defines a summary which can be used with <details> tag.
<sup>	It defines a text which is represented as superscript text.
<svg>	It is used as a container of SVG (Scalable Vector Graphics).
T	
<table>	It is used to present data in tabular form or to create a table within an HTML document.
<tbody>	It represents the body content of an HTML table and is used along with <thead> and <tfoot>.
<td>	It is used to define cells of an HTML table which contains table data
<template>	It is used to contain the client side content which will not display at time of page load and may render later using JavaScript.
<textarea>	It is used to define multiple line input, such as comment, feedback, and review, etc.
<tfoot>	It defines the footer content of an HTML table.
<th>	It defines the head cell of an HTML table.

<u><thead></u>	It defines the header of an HTML table. It is used along with <tbody> and <tfoot> tags.
<u><time></u> 	It is used to define data/time within an HTML document.
<u><title></u>	It defines the title or name of an HTML document.
<u><tr></u>	It defines the row cells in an HTML table
<u><track></u>	It is used to define text tracks for <audio> and <video> elements.
<u><tt></u>	It is used to define teletype text. (Not supported in HTML5)
U	
<u><u></u>	It is used to render enclosed text with an underline.
<u></u>	It defines an unordered list of items.
V	
<u><var></u>	It defines variable names used in mathematical or programming contexts.
<u><video></u> 	It is used to embed a video content with an HTML document

W

`<wbr>` 

It defines a position within text where a break line is possible.